

**1. THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE:** Dry pressed ceramic tiles with low water absorption  $E_b \leq 0,5\%$ ; Bla Group, glazed (GL)

**2. INTENDED USE OR USES:** For walls and floors internal and /or external, including stairs, in buildings and industrial facilities.

**3. MANUFACTURER:** CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce

**4. SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:** SYSTEM 4

**5. HARMONIZED STANDARD:** EN 14411:2012

**6. DECLARED PERFORMANCE:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE (LEVEL AND/OR CLASS)
<b>Reaction-to-fire performance</b>	A1 / A1 <sub>FL</sub> Classified Without Testing (CWT)
<b>Release of dangerous substances:</b>	
- Cadmium	$\leq 0,07 \text{ mg/dm}^2$
- Lead	$\leq 0,8 \text{ mg/dm}^2$
<b>Breaking strength:</b>	
- thickness <7,5mm	$\geq 700 \text{ N}$
<b>Bond strength/adhesion [N/mm<sup>2</sup>]:</b>	
- cementitious adhesives	$\geq 0,5 \text{ N/mm}^2$
- dispersion adhesives	$\geq 1 \text{ N/mm}^2$
- reaction resin adhesives	$\geq 2 \text{ N/mm}^2$
<b>Slippage according to CEN/TS 16165:2012, Annex B</b>	$\leq R13$
<b>Thermal shock resistance</b>	Pass
<b>Durability for:</b>	
- internal use:	Pass
- external use: resistance to freeze-thaw cycles	Pass
<b>Tactility</b>	NPD - No Performance Determined

A copy of the Declaration of Performance is available on the website: [www.cersanit.com](http://www.cersanit.com); [www.opoczno.eu](http://www.opoczno.eu)

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Place, date:  
Kielce, 01.04.2020

Signed on behalf of the manufacturer

QUALITY SYSTEM MANAGER  
  
Jolanta Grzebna