

1. **THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE:** 06/BIII/GL/CSE
2. **INTENDED USE OR USES:** Dry pressed ceramic tiles with water absorption $E_b > 10\%$; BIII Group, glazed (GL); for laying on walls indoors.
3. **MANUFACTURER:** CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce
4. **SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:** SYSTEM 4
5. **HARMONIZED STANDARD:** EN 14411:2012
6. **DECLARED PERFORMANCE:**

ESSENTIAL CHARACTERISTICS

PERFORMANCE (LEVEL AND/OR CLASS)

Reaction-to-fire performance	A1 Classified Without Testing (CWT)
Release of dangerous substances:	
- Cadmium	$\leq 0,07 \text{ mg/dm}^2$
- Lead	$\leq 0,8 \text{ mg/dm}^2$
Bond strength/adhesion [N/mm²]:	
- cementitious adhesives	$\geq 0,5 \text{ N/mm}^2$
- dispersion adhesives	$\geq 1 \text{ N/mm}^2$
- reaction resin adhesives	$\geq 2 \text{ N/mm}^2$
Thermal shock resistance	Meets
Durability for:	
- internal use:	Meets
- external use: resistance to freeze-thaw cycles	Does not meet
Tactility	NPD - No Performance Determined

A copy of the Declaration of Performance is available on the website: www.cersanit.com; www.opoczno.eu

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Place, date:
Kielce, 01.10.2018

Signed on behalf of the manufacturer

QUALITY SYSTEM MANAGER


Jolanta Grzebna