

1. THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE: 02/Bla/UGL/CSE

2. INTENDED USE OR USES: Dry pressed ceramic tiles with low water absorption $E_b \leq 0,5\%$; Bla Group, unglazed (UGL); polished; for laying on floors and/or walls indoors and laying on walls outdoors.

3. MANUFACTURER: CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce

4. SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE: SYSTEM 4

5. HARMONIZED STANDARD: EN 14411:2012

6. DECLARED PERFORMANCE:

| ESSENTIAL CHARACTERISTICS | PERFORMANCE (LEVEL AND/OR CLASS) |
|---|--|
| Reaction-to-fire performance | A1 _{FL} Classified Without Testing (CWT) |
| Release of dangerous substances: | |
| - Cadmium | $\leq 0,07 \text{ mg/dm}^2$ |
| - Lead | $\leq 0,8 \text{ mg/dm}^2$ |
| Breaking strength: | |
| - thickness $\geq 7,5 \text{ mm}$ | $\geq 1300 \text{ N}$ |
| - thickness $< 7,5 \text{ mm}$ | $\geq 700 \text{ N}$ |
| Bond strength/adhesion [N/mm²]: | |
| - cementitious adhesives | $\geq 0,5 \text{ N/mm}^2$ |
| - dispersion adhesives | $\geq 1 \text{ N/mm}^2$ |
| - reaction resin adhesives | $\geq 2 \text{ N/mm}^2$ |
| Slippage according to CEN/TS 16165:2012, Annex B | NPD - No Performance Determined |
| Thermal shock resistance | Meets |
| Durability for: | |
| - internal use: | Meets |
| - external use: resistance to freeze-thaw cycles | Meets |
| Tactility | NPD - No Performance Determined |

A copy of the Declaration of Performance is available on the website: www.cersanit.com; www.opoczno.eu

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Place, date:
Kielce, 01.10.2018

Signed on behalf of the manufacturer

QUALITY SYSTEM MANAGER

Jolanta Grzebna