

1. **THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE:** 05/BIIa/GL/CSE
2. **INTENDED USE OR USES:** Dry pressed ceramic tiles with water absorption $3\% < E_b \leq 6\%$; BIIa Group, glazed (GL); for laying on floors and/or walls indoors.
3. **MANUFACTURER:** CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce
4. **SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:** SYSTEM 4
5. **HARMONIZED STANDARD:** EN 14411:2012
6. **DECLARED PERFORMANCE:**

ESSENTIAL CHARACTERISTICS

PERFORMANCE (LEVEL AND/OR CLASS)

Reaction-to-fire performance	A1 _{FL} Classified Without Testing (CWT)
Release of dangerous substances:	
- Cadmium	≤ 0,07mg/dm ²
- Lead	≤ 0,8mg/dm ²
Breaking strength:	
- thickness ≥ 7,5mm	≥ 1000 N
- thickness < 7,5mm	≥ 600 N
Bond strength/adhesion [N/mm²]:	
- cementitious adhesives	≥ 0,5 N/mm ²
- dispersion adhesives	≥ 1 N/mm ²
- reaction resin adhesives	≥ 2 N/mm ²
Slippage according to CEN/TS 16165:2012, Annex B	≤ R13
Thermal shock resistance	Meets
Durability for:	
- internal use:	Meets
- external use: resistance to freeze-thaw cycles	Does not meets
Tactility	NPD - No Performance Determined

A copy of the Declaration of Performance is available on the website: www.cersanit.com; www.opoczno.eu

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Place, date:
Kielce, 01.10.2018

Signed on behalf of the manufacturer

QUALITY SYSTEM MANAGER

Jolanta Grzebna