

1. **THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE:** 08/Bib/GL/CSE
2. **INTENDED USE OR USES:** Dry pressed ceramic tiles with low water absorption  $0,5\% \leq E_b < 3\%$ , Bib Group, glazed (GL); Clinker, for laying on floors and/or walls indoors and/or outdoors.
3. **MANUFACTURER:** CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce
4. **SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:** SYSTEM 4
5. **HARMONIZED STANDARD:** EN 14411:2012
6. **DECLARED PERFORMANCE:**

**ESSENTIAL CHARACTERISTICS**

**PERFORMANCE (LEVEL AND/OR CLASS)**

<b>Reaction-to-fire performance</b>	A1 <sub>FL</sub> Classified Without Testing (CWT)
<b>Release of dangerous substances:</b>	
- Cadmium	≤ 0,07mg/dm <sup>2</sup>
- Lead	≤ 0,8mg/dm <sup>2</sup>
<b>Breaking strength:</b>	
- thickness ≥ 7,5mm	≥ 1100 N
- thickness < 7,5mm	≥ 700 N
<b>Bond strength/adhesion [N/mm<sup>2</sup>]:</b>	
- cementitious adhesives	≥ 0,5 N/mm <sup>2</sup>
- dispersion adhesives	≥ 1 N/mm <sup>2</sup>
- reaction resin adhesives	≥ 2 N/mm <sup>2</sup>
<b>Slippage according to CEN/TS 16165:2012, Annex B</b>	≤ R13
<b>Thermal shock resistance</b>	Meets
<b>Durability for:</b>	
- internal use:	Meets
- external use: resistance to freeze-thaw cycles	Meets
<b>Tactility</b>	NPD - No Performance Determined

A copy of the Declaration of Performance is available on the website: [www.cersanit.com](http://www.cersanit.com); [www.opoczno.eu](http://www.opoczno.eu)

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Place, date:  
Kielce, 01.10.2018

Signed on behalf of the manufacturer

QUALITY SYSTEM MANAGER  
  
Jolanta Grzebna